

Hand-held joint cutter HFS 150

ALMOST
DUST
FREE

www.frueh-maschinen.de

The **HFS 150** is a handy, movable and stable joint cutter for cutting in floors with and without chamfer.

Technical Data:

Voltage	230 Volt
Power	1,4 kW
Speed	4.000-9.000 min ⁻¹
Cutting disc	Ø 150 mm
Cutting depth	40 mm max.
Holding flange	27 mm
Cutting width	20 mm max.
Cutting grooves	25 mm max.
Dust extraction connection	Ø 38 mm
Weight	9,3 kg



Areas of application:


- Cutting in screed and concrete
- Recutting joints
- Chamfering existing joints (on one or on both sides)
- Cutting joints open and chamfering simultaneously

Erwin Früh GmbH


Machines and accessories for professional floor treatment and sub-floor preparation
Vorstadtstraße 61-67, DE-73614 Schorndorf info@frueh-maschinen.de
Phone + 49 7181 92 97 32, Fax + 49 7181 92 97 33




HFS 150 tools and accessories



1. Diamond cutting disc `Abrasives`
Ø 150 mm
Part no. 232.304
 10 mm segment height,
 bore hole 22,23 mm,
 with core protection segment,
 for epoxy mortar, screeds and coatings



2. Diamond cutting disc `Concrete`
Ø 150 mm
Part no. 239.158
 10 mm segment height,
 bore hole 22,23 mm,
 for concrete, reinforced concrete, aggregate
 concrete, common construction material




3. Diamond cutting disc `Twister Plus 12`
Ø 150 mm
Part no. 232.305
 12 mm segment height, bore hole 22,23 mm,
 long service life, self-cooling,
 for concrete, hard old concrete, reinforced
 concrete, industrial screeds, roof tiles, hard
 clinker, medium hard clinker, aggregated
 concrete, general purposes, granite



4. Chamfer disc FF-90
Ø 130 mm
Part no. 233.125
 Bore hole 22,23 mm,
 max. 7 mm wide chamfer for chamfering
 joints of concrete and screed,
 chamfering on one side = one chamfer disc +
 cutting disc(s),
 chamfering on both sides = two chamfer
 discs + cutting disc(s)



5. Truing stick silicon carbide
Part no. 332.484
 For truing chamfer disc FF-90



6. Vulkollan® sealing set
Part no. 332.001
 for dust extraction hood
 1 x Vulkollan® lip seal (36 x 40 x 2 mm)
 1 x clamping plate (35 x 15 x 1 mm)
 2 x blind rivet 4 mm




Scope of delivery HFS 150, part no. 032.300
 Machine with cutting disc `Concrete` Ø 150 mm,
 dust protection guard, depth control stop, distance
 washers, antivibration grip, assembly tools.
 All supplied in a transport system.



7. Distance washer thick
Ø 48,5 x 5 mm
Part no. 332.501
 For positioning and tightening the
 cutting discs on the holding flange



8. Distance washer thin
Ø 48,5 x 2,5 mm
Part no. 332.500
 For positioning and tightening the
 cutting discs on the holding flange



9. Distance washer small
Ø 36 x 1 mm
Part no. 332.502
 For mounting between the cutting
 discs if cutting wide joints with
 several cutting discs

Erwin Früh GmbH

Machines and accessories for professional floor treatment and sub-floor preparation
 Vorstadtstraße 61-67, DE-73614 Schorndorf info@frueh-maschinen.de
 Phone + 49 7181 92 97 32, Fax + 49 7181 92 97 33 www.frueh-maschinen.de

